



VS-44AV

**SWITCHERS, MATRIX
SWITCHERS &
CONTROLLERS**

4X4 COMPOSITE VIDEO & STEREO AUDIO MECHANICAL SWITCHER



SPECIFICATIONS

INPUTS:	4 video, 1Vpp/75Ω on BNC connectors. 4 audio stereo, up to 36Vpp (typ.) on RCA connectors.
OUTPUTS:	4 composite video, 1Vpp/75Ω on BNC connectors. 4 stereo audio, up to 36Vpp (typ.) on RCA connectors.
SWITCHING SYSTEM:	Mechanical, Break-before-Make.
BANDWIDTH (-3DB):	Video: 220MHz. Audio: 100 kHz.
CROSSPOINTS:	16 for video, 16x2 for audio, 4 active at any given time.
VIDEO CROSSTALK:	-46dB @ 5MHz.
DIMENSIONS:	19 inch (W), 4 inch (D), 1U (H) rack mountable.
WEIGHT:	1.6kg. (3.5lbs) approx.

DESCRIPTION

The VS-44AV is a high performance switcher (4 crosspoints) for composite video and unbalanced stereo audio signals. It can route up to four inputs to four different outputs, but it can not distribute any one signal to multiple outputs.

- Bandwidth - 220MHz (-3dB).
- Mechanical (Passive) Switching - No power required.
- Standard 19" Rack Mount Size - 1U.

