



PLC-XU350

- Brightness: 3500 ANSI Lumen
- XGA Resolution
- Auto Setup
- Pin Code Security
- Easy Lamp Access
- Network Monitoring and Control (RJ45)

PLC-XU350

TECHNICAL DETAILS	PLC-XU350
Category	Business & Education
Panel	3 x 0.63" TFT Polysilicon (4:3)
Lamp	225W UHP
Brightness ANSI lumens	3500
Lamp Service Life	2500h (Eco Mode), 2000h (Normal Mode)
Fan Noise	29dBA (Eco Mode), 34dBA (Normal Mode)
Standard Lens	F= 1.6-1.76, f=22.3-26.8mm
Throw Distance Ratio	1.72-2.07:1
Throw Distance	1.39-12.7m
Contrast Ratio	500:1
Resolution in pixels	786,432 (1024 x 768)
Image size min-max (diagonal)	40"-300"
Uniformity	85%
Bandwidth/Frequency	140MHz, Horizontal 15kHz-100kHz, Vertical 50Hz-100Hz
Colour Systems	NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-N
Connections	Input 1: 1 x Dsub15 (RGB, Component, Scart RGB) Input 2: 1 x Dsub15 (Switchable) Input 3: 1 x RCA (Composite Video) Input 4: 1 x Mini DIN 4-PIN (S-Video) Audio input: 2 x RCA Audio Input: 1 x Mini Jack Control: 1 x RJ45 (Wired LAN) Control: 1 x Dsub9 (RS232)
Keystone Correction	Vertical $\pm 30^\circ$
HDTV Signals	575p / 720p / 1080i
Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC
Zoom/Focus	1.2x / Manual
Power Consumption/Voltage	225W (Eco Mode), 287W (Normal Mode), 3.2W (Standby Mode)
Warranty	3 Year
Dimensions (W x H x D)	326 x 92.6 x 231.6mm
Weight	2.6kg
Standard Accessories	Quick Reference Guide, User Manual (CD ROM), Computer Cable (Dsub15-Dsub15), Power Cable, Remote Control, PJ Network Manager Software (CD ROM), Soft Carry Bag
Optional Accessories	POA-CA-COMPVGA (Component- Dsub15 Cable), POA-CA-SCART (Scart-Dsub15 Cable)

* You can use the distance calculator at <http://uk.sanyo.com> to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 04/2009

